

POLYSTICK® TU MAX

Roof Underlayment

General Specifications

- Polyester surface reinforcement APP modified asphalt for exceptional performance
- Building code compliant 60 mil nominal thickness
- Extended exposure to the elements to 180 days
- Features patented Seallap®, a factory applied adhesive treatment at the membrane side lap



Approvals

- Miami-Dade County Approval # 09-0806.07
- Florida Building Code Approved



Contact your roofing contractor today and ask for Polystick TU MAX.

POLYGLASS®



polyglass.us

1-800-222-9782

Providing *Peace of Mind...*



POLYSTICK[®]TU MAX

Waterproofing for Your Tile Roof

- Designed for high temperature roof systems
- Durable and tear resistant
- Manufactured in Florida
- Self-adhered roof underlayment for fast and easy installation
- Proven hurricane protection
- Clean, odor-free and non-intrusive product made using recycled materials
- Up to 30 year manufacturer's warranty



Polystick TU MAX is a high performance roof underlayment manufactured using Polyglass' industry recognized Self-Adhesive technology. Manufactured with a durable, slip-resistant, polyester fabric surface and an aggressive self-adhesive compound on the bottom surface, Polystick TU MAX is ideally suited as an underlayment for concrete or clay tile roofing.

POLYSTICK[®]