

SECTION 1 PRODUCT NAME AND COMPANY IDENTIFICATION

Product Name: Fast Drying Asphalt Primer PG100

Recommended Use: Roofing and other construction applications.

Restriction on Use: None

Manufacturer:

Polyglass U.S.A. Inc.
 1111 West Newport Center Drive
 Deerfield Beach, Florida 33442
 866-222-9782

SDS Date of Preparation: 05/17/2018

Emergency Contact: (800) 424-9300 CHEMTREC (USA)

SECTION 2: HAZARDS IDENTIFICATION

Hazard Classification:

Physical	Health
Flammable Liquid Category 3	Skin Irritation Category 2 Specific Target Organ Toxicity Single Exposure Category 3 (narcotic effects) Specific Target Organ Toxicity Repeated Exposure Category 1 (nervous system)

Label Elements:

DANGER!
 Flammable liquid and vapor.
 Causes skin irritation.
 May cause drowsiness or dizziness.
 Causes damage to nervous system through prolonged or repeated exposure.



Prevention

Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
 Keep container tightly closed.
 Ground and bond containers and receiving equipment.
 Use explosion-proof electrical, ventilating and lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe vapors.
 Use only outdoors or in a well-ventilated area.
 Wash thoroughly after handling.
 Wear protective gloves and eye protection.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 If skin irritation occurs: Get medical attention.
 Wash contaminated clothing before reuse.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.
 In case of fire: Use water fog, carbon dioxide, dry chemical or foam to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool.

Disposal:

Dispose of contents and container in accordance with local and national regulations.



Safety Data Sheet

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENTS</u>	<u>CAS#</u>	<u>WT.%</u>
Asphalt	8052-42-4 64742-93-4	30-60
Mineral Spirits	8052-41-3	30-60
1,2,4-Trimethylbenzene	95-63-6	1-2%

The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURES

Eyes: Immediately flush eyes with water for at least 15 minutes while lifting the upper and lower lids. Get medical attention if irritation persists.

Skin: Remove contaminated clothing. Wash skin thoroughly with soap and water. If rash or irritation develops, get medical attention. Launder clothing before re-use. (Discard contaminated shoes).

Inhalation: Remove victim to fresh air. If breathing has stopped give artificial respiration. If breathing is difficult have qualified personnel administer oxygen. Get immediate medical attention.

Ingestion: If conscious, rinse mouth with water. Do not induce vomiting. Never give anything by mouth to a person who is unconscious or convulsing. Get immediate medical attention.

Most important symptoms/effects, acute and delayed: Causes skin irritation. Vapors and mists may cause mucous membrane and upper respiratory tract irritation with headache, dizziness, drowsiness, nausea and unconsciousness. Prolonged and/or repeated overexposure may cause liver, kidney, and nervous system damage.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention if needed for severe inhalation exposures and all ingestions.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Use water fog, carbon dioxide, dry chemical or foam. Cool fire exposed containers with water

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Do not allow run-off from firefighting to enter drains or water courses

Specific Hazards Arising from the Chemical: Flammable liquid and vapor. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back. Closed containers may explode if exposed to extreme heat. Combustion products may include oxides of carbon and sulfur, hydrogen sulfide, sulfur dioxide and hydrocarbons.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Wear appropriate protective clothing to prevent eye and skin contact. Evacuate and ventilate area using explosion proof equipment. Remove all ignition sources such as flames, hot surfaces, pilot lights and spark producing equipment.

Environmental precautions: Avoid release to the environment. Report releases as required by local, state and federal authorities.

Methods and Materials for Containment and Cleaning Up: Collect spilled material with inert material and place into a closable container for disposal.

SECTION 7 HANDLING and STORAGE

Precautions for Safe Handling: Avoid contact with the eyes, skin and clothing. Avoid breathing vapors. Wear protective clothing and equipment as described in Section 8. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep product away from heat, sparks, flames and all other sources of ignition. Do not permit smoking in use or storage areas.

Do not cut, drill, grind or weld on or near containers, even empty containers. Empty containers retain product residues can be hazardous. Follow all MSDS precautions when handling empty containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a dry, well-ventilated area away from heat, direct sunlight and all sources of ignition and oxidizing agents.

SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

Exposure Guidelines:

INGREDIENTS	EXPOSURE LIMITS
Asphalt	0.5 mg/m ³ TWA ACGIH TLV (as asphalt fume)
Mineral Spirits	500 ppm TWA OSHA PEL 100 ppm TWA ACGIH TLV
1,2,4 Trimethylbenzene (as trimethylbenzenes)	25 ppm TWA ACGIH TLV

Appropriate Engineering Controls: Use with adequate ventilation to maintain exposures below the occupational exposure limits. Use explosion proof equipment.

Respiratory Protection: If the exposure limits are exceeded a NIOSH approved respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Gloves: Nitrile or other impervious gloves are recommended to prevent skin contact.

Eye Protection: Chemical safety goggles should be worn if splashing is possible.

Other Protective Equipment: Impervious clothing as needed to prevent contact. For operations where contact can occur, washing facilities should be available.

SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

Appearance And Odor: Black liquid with a solvent odor.

Boiling Point (@ 760 mmHg): 310-400°F (154-204°C)	Freezing Point: Not available
Odor Threshold: Not available	Viscosity: 2000 cP @ 25°C
Relative density (H₂O=1): 1.10	Vapor Pressure: 2 mmHg @ 68°F
VOC: 350 g/L (2.9 lbs/gal)	Vapor Density (AIR=1): >1
Evaporation Rate: Not available	Solubility In Water: Insoluble in water
pH: Not applicable	Partition Coefficient n-Octanol/Water: Not determined
Flash Point: 105°F (40.5°C)	Autoignition Temperature: Not available
Decomposition Temperature: Not available	Flammability (solid, gas): Not applicable
Flammable Limits: (vol % in air)	LEL – 1.1%(mineral spirits) UEL – 6.0% (mineral spirits)



Safety Data Sheet

SECTION 10 STABILITY and REACTIVITY

Reactivity: Not normally reactive.

Chemical Stability: Stable under normal storage and handling conditions

Possibility of Hazardous Reactions: None known

Conditions to avoid: Avoid heat, sparks, flames and all other sources of ignition.

Incompatible materials: Avoid oxidizing agents and water.

Hazardous decomposition products: Thermal decomposition may yield oxides of carbon and sulfur, hydrogen sulfide, sulfur dioxide and hydrocarbons.

SECTION 11 TOXICOLOGICAL INFORMATION

Eye: Contact may cause irritation with redness and tearing.

Skin: Contact may cause irritation, drying and dermatitis.

Inhalation: Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, nausea, vomiting, disorientation, stupor and unconscious. Severe overexposures may cause respiration depression and death. Hydrogen sulfide will evolve from asphalt and collect in the headspace of containers. Hydrogen sulfide is irritating to the eyes and respiratory tract at low concentrations. High concentrations of hydrogen sulfide can cause respiratory arrest and death.

Ingestion: Ingestion may cause mucous membrane and gastrointestinal irritation and nervous system depression with symptoms of headache, dizziness, nausea, narcosis and unconsciousness.

Sensitization: This product is not expected to cause sensitization.

Chronic Effects: Prolonged overexposure may cause damage to the nervous system, blood system, liver and kidneys.

Carcinogenicity: None of the components present at 0.1% or greater are listed as a carcinogen by NTP, IARC, ACGIH or OSHA.

Numerical Measures of Toxicity:

Asphalt: Oral Rat LD50 >5000 mg/kg; dermal rabbit LD50 > 2000 mg/kg

Mineral Spirits: Oral rat LD50 >5000mg/kg dermal LD50 rabbit >2000 mg/kg, inhalation rat LC50 >7.63 mg/L (no mortality)

1,2,4 Trimethylbenzene: Oral rat LD50 3280 mg/kg; Skin rabbit >3160 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Mineral Spirits: The 96-h LC₅₀ values for fish (*Pimephales promelas*) was within the range of 4.2-20.8 and fish (*Lepomis macrochirus*) was within the range of 2.1-4.2 mg/liter

The 48-h LC₅₀ for *Daphnia magna* was within the range of 0.42-2.3 mg/liter

Asphalt: Toxicity in fish, daphnia and algae is estimated >1000 mg/L

Persistence and degradability: Stoddard solvent is readily biodegradable. Asphalt is not biodegradable.

Bioaccumulative potential: Based on the calculated log Kow >3, Stoddard has some potential to bioaccumulate.

Mobility in soil: No data available.

Other adverse effects: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with all local, state and federal regulations.

SECTION 14: TRANSPORT INFORMATION

DOT/TDG (Non-Bulk): Not regulated (if shipped in NON BULK package, (119 gallon or less) by ground)



Safety Data Sheet

DOT/TDG (Bulk): **If shipped in containers greater than 119 gallons (889 lbs.)**
UN/ID Number UN1999
Proper Shipping Name Tars, liquid
Hazard Class 3
Packing Group III
ERG Code 130
DOT Special Provisions B1, B13, IB3, T1, TP3
Description UN1999, Tars, liquid, 3, III

DOT/TDG (Elevated Temperature): If shipped BULK at Elevated Temperature (above the flashpoint of 105°F/40.5°C)
UN/ID Number UN3256
Proper Shipping Name Elevated temperature, liquid, flammable, n.o.s. (Petroleum Distillates)
Hazard Class 3
Packing Group III
ERG Code 128
DOT Special Provisions IB1, T3, TP3, TP29
TDG Special Provisions 16
Description UN3256, Elevated temperature, liquid, flammable, n.o.s. (Petroleum Distillates), 3, III

IATA:
UN/ID Number UN1999
Proper Shipping Name Tars, liquid
Hazard Class 3
Packing Group III
ERG Code 3L
Special Provisions A3
Description UN1999, Tars, liquid, 3, III

IMDG: Non-regulated per 2.3.2.5
UN/ID Number UN1999
Proper Shipping Name Tars, liquid
Hazard Class 3
Packing Group III
EmS-No F-E,S-E
Special Provisions 955
Description UN1999, Tars, liquid, 3, III, FP 40.5°C

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None known

SECTION 15: REGULATORY INFORMATION

SARA Hazard Category (311/312): Acute Health, Chronic Health, Fire Hazard.

EPA SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313:

1,2,4 Trimethylbenzene	95-63-6	1-2%
------------------------	---------	------

CERCLA Hazardous Substances (Section 103)/RQ: This product is not subject to CERCLA reporting requirements, however, oil spills are reported to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory.



Safety Data Sheet

California Proposition 65: This product may contain chemicals known to the State of California to cause cancer or reproductive toxicity.

WHMIS Classification: Class B Division 3 (Combustible Liquid); Class D Division 2 Subdivision B (Toxic Material Causing other Toxic Effects)

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

SECTION 16: OTHER INFORMATION

NFPA Rating:	Health = 2	Fire = 2	Instability = 0
HMIS Rating:	Health = 2	Fire = 2	Physical Hazard = 0

SDS Date of Preparation: 05/17/18

Revision Summary: Revised Section 14.

NOTICE

This above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Polyglass U.S.A. Inc. shall not be held liable for any damage resulting from handling or from contact with the above product. This information relates only to the product designated herein and does not relate to its use in combination with any other material or process.