

GRANULES

PRODUCT DESCRIPTION

Polyglass Granules are high quality mineral granules as used on mineral-surfaced membrane products. They are tough, dense, ceramic-coated particles that are weather and UV resistant. Polyglass Granules are composed of a granite-like mineral permanently coated with various pigments to match Polyglass membrane products.

USES

- Apply to areas of exposed hot asphalt or adhesive.
- Apply to areas of bleed-out on torch-applied membranes.
- Apply to exposed asphaltic mastic.
- Typically broadcasted at approximately 4 ft² per pound (200 ft² for 50 lb pail) depending on the overall density desired.

FEATURES AND BENEFITS

- Quality particles – strong, dense, and non-porous
- Aids in prevention of damage from hail and environmental contaminants
- Available in a variety of colors

Black	Buff	Chestnut	Oak
Grey Slate	White	Red Blend	Pine Green
Heather Blend	Weatherwood	Bright White	

APPLICATION INSTRUCTIONS

- Apply while asphalt is hot if materials are fluid.
- Press into the surface to ensure adhesion

For Professional Use Only - Keep out of the reach of children.

WARNING

Wear eye protection. Avoid creating dust. Take care not to distribute granules off roof when applying.

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.

1111 West Newport Center Drive

Deerfield Beach, FL 33442

www.polyglass.us

General Line: (888) 410-1375

(954) 233-1330

Customer Service: (800) 222-9782

Technical Service: (866) 794-9659

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects that result in the material not complying with product specifications for a period of 12 months.

Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances. The product user, and not Polyglass, is responsible for determining the suitability and compatibility of our products for the user's intended use.

For the most current product data and warranty information, visit
www.polyglass.us

PACKAGING

- 50 lb Pail