Safety Data Sheet

POLYBRITE 97X - EPOXY PRIMER PART B

Safety Data Sheet dated: 02/14/2023 - version 1

Date of first edition: 02/14/2023



1. Identification

Product identifier

Mixture identification:

Trade name: POLYBRITE 97X - EPOXY PRIMER PART B

Trade code: PLY0078

Recommended use and restrictions on use

Recommended use: Primer Restrictions on use: Not available

Supplier's details

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive 33442 - Deerfield Beach - FL - USA

Phone: +1 866-222-9782 Responsable: info@polyglass.com

Emergency phone number

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887 Emergency Transport CANUTEC (Canada) 1-613-996-

6666

2. Hazard identification









Classification of the product

Flammable Liquids — Category 3 Flammable liquid and vapour.

Skin irritation, Category 2 Causes skin irritation.

Serious eye damage, Category 1 Causes serious eye damage.

Carcinogenicity, Category 1B May cause cancer if inhaled, in contact with skin and if

swallowed.

Chronic (long-term) aquatic hazard - Category 2

Toxic to aquatic life with long lasting effects.

Label elements

Pictograms and Signal Words





Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H350 May cause cancer if inhaled, in contact with skin and if swallowed.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P233 Keep container tightly closed.

Ground and bond container and receiving equipment. P240

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges. P264 Wash hands thoroughly after handling.

Print date 02/14/2023 **Production Name** POLYBRITE 97X - EPOXY PRIMER PART B Page n.



P273 Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. P280 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P303+P361+P353 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P310 Immediately call a doctor. P321 Specific treatment (see supplementary instructions on this label) P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish. P391 Collect spillage. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container in accordance with applicable regulations.

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

3. Composition/information on ingredients

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
25-50 %	fatty acids, c18-unsaturated, dimers, reaction products with polyethylenepolyamines; polyethylene polyamine, dimer fatty acid condensate	CAS:68410-23-1 EC:614-452-7	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Chronic 2, H411	
25-50 %	naphthenic oil; Low boiling point naphtha - unspecified		Asp. Tox. 1, H304; Flam. Liq. 3, H226; Carc. 1B, H350	
0.49-1 %	carbon black; acetylene black	CAS:1333-86-4 EC:215-609-9	Comb. Dust, CANH003	

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

02/14/2023 Production Name POLYBRITE 97X - EPOXY PRIMER PART B Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

(see paragraph 4.1)

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

CO2 or Dry chemical fire extinguisher.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Wash skin thoroughly after handling.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Electrical installations / working materials must comply with the technological safety standards.

Ground/bond container and receiving equipment.

02/14/2023 Production Name POLYBRITE 97X - EPOXY PRIMER PART B Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. Exposure controls/personal protection **Control parameters**

Community Occupational Exposure Limits (OEL)

OEL **Occupational Exposure Limit**

Type

carbon black; acetylene black OSHA Long Term: 3.5 mg/m3

CAS: 1333-86-4

ACGIH Long Term: 3 mg/m3

A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans; bronchitis;

ACGIH Long Term: 3 mg/m3

A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans:bronchitis

Appropriate engineering controls

Not available

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid Grey

Odour: solvent like

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available Initial boiling point and boiling range: No data available

Flash point: 60 °C (140 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 1.39 g/cm3

Solubility in water: No data available Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: 280.00 °C

Decomposition temperature: No data available

Print date 02/14/2023 **Production Name** POLYBRITE 97X - EPOXY PRIMER PART B Page n.

4 of

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None

11. Toxicological information

Information on toxicological effects

Likely routes of exposure:

Skin contact, skin absorption, eye contact, inhalation and ingestion.

Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation The product is classified: Skin irritation, Category 2(H315)

The product is classified: Serious eye damage, Category 1(H318) c) serious eye damage/irritation

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity The product is classified: Carcinogenicity, Category 1B(H350)

g) reproductive toxicity

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

naphthenic oil; Low boiling point naphtha - a) acute toxicity

LD50 Skin Rabbit > 2000 mg/kg

unspecified

LC50 Inhalation Rat = 3400 ppm 4h

LD50 Oral Rat = 8400 mg/kg

carbon black; acetylene a) acute toxicity

black

LD50 Oral Rat > 15400 mg/kg

LD50 Skin Rabbit > 3 g/kg LD50 Oral Rat > 15400 mg/kg

Print date 02/14/2023 **Production Name** POLYBRITE 97X - EPOXY PRIMER PART B 5 of Page n.

Substance(s) listed on the IARC Monographs:

carbon black; acetylene black Group 2B

Substance(s) listed as OSHA Carcinogen(s):

carbon black; acetylene black

Substance(s) listed as NIOSH Carcinogen(s):

carbon black; acetylene black

Substance(s) listed on the NTP report on Carcinogens:

None

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of Eco-Toxicological properties of the product

The product is classified: Chronic (long-term) aquatic hazard - Category 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Component	Tuent, Numb.	LCUIUX Dala

naphthenic oil; Low boiling point naphtha - unspecified

CAS: 64742-95- G: LC50 Avian Colinus virginianus > 6500 ppm 5d IUCLID 6 - EINECS: 265-199-0 -INDEX: 649-356-00-4

G: LD50 Avian Colinus virginianus > 2250 mg/kg IUCLID

a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss = 9.22 mg/L 96h

IUCLID

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 6.14 mg/L 48h

carbon black; acetylene black CAS: 1333-86-4 a) Aquatic acute toxicity: EC50 Daphnia Magna > 5600 mg/L 1333-86-4 -

- EINECS: 215-

609-9

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

14. Transport information

UN number

TDG-UN number: UN1993 ADR-UN number: 1993 DOT-UN Number: UN1993 IATA-Un number: 1993 IMDG-Un number: 1993

UN proper shipping name

TDG-Shipping Name: FLAMMABLE LIQUID, N.O.S. (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour

pressure at 50 °C more than 110 kPa, boiling point of more than 35 °C) (hydrocarbons, C9, aromatics - fatty acids, c18-unsaturated, dimers, reaction products with polyethylenepolyamines; polyethylene polyamine,

dimer fatty acid condensate)

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour

pressure at 50 °C more than 110 kPa, boiling point of more than 35 °C) (hydrocarbons, C9, aromatics - fatty acids, c18-unsaturated, dimers, reaction products with polyethylenepolyamines; polyethylene polyamine,

dimer fatty acid condensate)

DOT-Proper Shipping Name: Flammable liquids, n.o.s. (hydrocarbons, C9, aromatics - fatty acids, c18-unsaturated, dimers, reaction

products with polyethylenepolyamines; polyethylene polyamine, dimer fatty acid condensate)

IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (hydrocarbons, C9, aromatics - fatty acids, c18-unsaturated, dimers, reaction

products with polyethylenepolyamines; polyethylene polyamine, dimer fatty acid condensate)

IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (hydrocarbons, C9, aromatics - fatty acids, c18-unsaturated, dimers, reaction

products with polyethylenepolyamines; polyethylene polyamine, dimer fatty acid condensate)

Transport hazard class(es)

TDG-Class: 3

ADR-Class: 3

DOT-Hazard Class: 3

IATA-Class: 3 IMDG-Class: 3

Packing group

TDG-Packing Group: III ADR-Packing Group: III DOT Packing Group: III IATA-Packing group: III IMDG-Packing group: III

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: Not Applicable

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

Not Applicable

Special precautions in connection with transport or conveyance

TDG:

TDG Special provisions: 16

Department of Transportation (DOT):

DOT-Special Provision(s): B1, B52, IB3, T4, TP1, TP29

DOT-Label(s): 3 DOT-Symbol: N/A DOT-Cargo Aircraft: N/A DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A DOT-Non-Bulk: N/A Road and Rail (ADR-RID): ADR-Label: 3

ADR-Hazard identification number: -

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 355 IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 223 274 955

IMDG-Page: N/A IMDG-Label: N/A IMDG-EMS: F-E, S-E IMDG-MFAG: N/A

15. Regulatory information

Canada - Federal regulations

DSL - Domestic Substances List

DSL (Domestic Substances List)

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL (Non Domestic Substances List)

No substances listed

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

fatty acids, c18-unsaturated, dimers, reaction products with polyethylenepolyamines; polyethylene polyamine, dimer fatty acid condensate

is listed in TSCA Section 8b

naphthenic oil; Low boiling point

naphtha - unspecified

is listed in TSCA Section 8b

carbon black; acetylene black is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

02/14/2023 Production Name POLYBRITE 97X - EPOXY PRIMER PART B

Substance(s) listed under California Proposition 65:

carbon black; acetylene black Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

carbon black; acetylene black

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

carbon black; acetylene black

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

carbon black; acetylene black

16. Other information

Safety Data Sheet dated: 2/14/2023 - version 1

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial,

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
CANH003	May form combustible dust concentrations in air.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H350	May cause cancer.
H411	Toxic to aquatic life with long lasting effects.
Code	Hazard class and hazard category Description

A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.6/1B	Carc. 1B	Carcinogenicity, Category 1B
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3
CAN-ADD/CD	Comb. Dust	Combustible Dusts — Category 1
CAN-HAE/C2	Aquatic Chronic 2	Chronic (long-term) aquatic hazard - Category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

Print date

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Print date

02/14/2023

Production Name

POLYBRITE 97X - EPOXY PRIMER PART B

Page n.