

# POLYBRITE® REINFORCING FIBERGLASS ASPHALT SATURATED FABRIC

## PRODUCT DESCRIPTION

PolyBrite Reinforcing Fiberglass is woven fabric 20 x 10 mesh, made of yarns of inert, flexible filaments of pure glass saturated with asphalt.

## FEATURES AND BENEFITS

PolyBrite Reinforcing Fiberglass is designed for use in all Polyglass and PolyPlus Flashing Cements and Roof Cements when used in roof repair work, for flashings, and for sealing seams in metal composition roofs. PolyBrite Reinforcing Fiberglass has a tensile strength of 75 lb/in. PolyBrite Reinforcing Fiberglass is durable, flexible and will not decay from heat. Using PolyBrite Reinforcing Fiberglass results in lower cost on repairs compared to torched MB patches, heat sealed single ply patches and metal patches. One product fits most repairs.

Available in 4"x150' and 6"x150'. For other application questions, please contact Polyglass Technical Services at (866) 794-9659.

## MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

## CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.  
1111 West Newport Center Drive  
Deerfield Beach, FL 33442  
[www.polyglass.us](http://www.polyglass.us)

General Line: (888) 410-1375  
(954) 233-1330  
Customer Service: (800) 222-9782  
Technical Service: (866) 794-9659

**Questions?** [technical@polyglass.com](mailto:technical@polyglass.com)

**Product Disclaimer:** Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects that result in the material not complying with product specifications for a period of 12 months.

Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances. The product user, and not Polyglass, is responsible for determining the suitability and compatibility of our products for the user's intended use.

**For the most current product data and warranty information, visit [www.polyglass.us](http://www.polyglass.us)**



## APPLICABLE STANDARDS

- ASTM D1668, Type I.



## PACKAGING

- 4" x 150 Linear Feet Rolls
- 6" x 150 Linear Feet Rolls

## COLORS

Black



**POLYGLASS®**



[www.polyglass.us](http://www.polyglass.us)