

# POLYGLASS DETAIL & REPAIR FINISH

## FEATURING CURE TECHNOLOGY®

### PRODUCT DESCRIPTION

Polyglass Detail & Repair Finish featuring CURE Technology is a highly reflective coating formulated specially to address the installation and system repair needs of Polyglass membranes manufactured with CURE Technology. Designed to extend the life and enhance the performance of the roof system, Polyglass Detail & Repair Finish is bright white and will complement the aesthetic beauty of Polyglass Kool Roofing membranes.

Polyglass Detail & Repair Finish can be used to touch-up all flashing details, and can also be used to coat standard granules used at seam bleed-out and repairs to unify and beautify the roof appearance. In addition to having a reflectivity greater than 74%, Polyglass Detail & Repair Finish will enhance granule retention and provide improved abrasion and scuff resistance. Polyglass Detail & Repair Finish is water based and environmentally friendly.

### APPLICATION GUIDELINES

Polyglass Detail & Repair Finish is designed to be spray applied over the roofing surface. The viscosity, solids and overall formulation has been optimized to be applied over these uneven surfaces.

The finish touch-up can be applied using various equipment including conventional airless (or air-assist) sprayers, garden style pump sprayers, brush or rollers.

It is estimated when using Polyglass Detail & Repair Finish, that normal spray touch-up at the side and end lap seams of the membrane, should cover proximately 20 – 25 rolls when applied at 2 mils (50 microns) dry film thickness. Thicker application rate will reduce number of rolls covered per gallon.

Polyglass Detail & Repair Finish is available in 1-gallon cans, or 5-gallon pails; estimated coverage is 1 gallon per 100 square feet of coverage at an estimated thickness of 50 microns (2 mils).

### MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Winter Haven, FL

### CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.  
1111 West Newport Center Drive  
Deerfield Beach, FL 33442  
www.polyglass.us  
General Line: (888) 410-1375  
(954) 233-1330  
Customer Service: (800) 222-9782  
Technical Service: (866) 802-8017

**Questions?** [technical@polyglass.com](mailto:technical@polyglass.com)

**Product Disclaimer:** Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects in its product that directly results in leakage for a period of 1 year.

Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control. For most current product data and warranty information, visit [www.polyglass.us](http://www.polyglass.us)



### PRODUCT DATA

Coverage (Approx) .... 1 gal / 500 sq ft  
Weight..... 11 lbs / gal  
Size..... 1 gal can or 5 gal pail

### PRODUCT WARRANTY

Polyglass U.S.A., Inc. commercial roofing membranes can be backed with a manufacturer's warranty for up to 20 years when used as part of an approved, multi-ply roofing system. Please see your Polyglass U.S.A., Inc. Sales or Technical Representative for specifications and details.

ACCESSORIES



[www.polyglass.us](http://www.polyglass.us)