

POLYBRITE® REINFORCING POLYESTER

STITCHBONDED POLYESTER FABRIC

PRODUCT DESCRIPTION

PolyBrite Reinforcing Polyester is a white, 3 ounce stitchbonded polyester fabric used in the reinforcement of cold process roofing systems and also as a reinforcement with elastomeric coatings and mastics. The flexible nature of this fabric also allows for ease of application over the critical corrugations and laps found in metal roofing and conforms with smooth and semi-smooth surfaces.

TYPICAL PHYSICAL PROPERTIES

TEST PROPERTY	TEST VALUE	TEST PROCEDURE
Tensile Strength (lb)	55 - MD 60 - XMD	ASTM D5034
Trapezoid Tear (lb)	20 - MD 20 - XMD	ASTM D5587
Elongation (lb)	25 - MD 100 - XMD	ASTM D5034
Thickness (in.)	0.018	ASTM D1777
Ball Burst (lb)	90	ASTM D3787

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442

www.polyglass.us

General Line: (888) 410-1375
(954) 233-1330

Customer Service: (800) 222-9782

Technical Service: (866) 794-9659

Questions? technical@polyglass.com

For the most current product data and warranty information, visit www.polyglass.us



APPLICABLE STANDARDS

- FM Approved



PACKAGING

- 4" x 300' Roll
- 6" x 300' Roll
- 12" x 180' Roll
- 12" x 300' Roll
- 20" x 300' Roll
- 40" x 324' Roll
- 40" x 324' Roll (Firm)

COLORS

White



POLYGLASS®



www.polyglass.us