

POLYBRITE®

REINFORCING POLYESTER

PRODUCT DESCRIPTION

Polybrite Polyester Fabric* is a white, 3 ounce stitchbonded polyester fabric used in the reinforcement of cold process roofing systems and also as a reinforcement with mastics and elastomerics. The flexible nature of this fabric also allows for ease of application over the critical corrugations and laps found in metal roofing and conforms with smooth and semi-smooth surfaces. This product may require light brooming to insure good embedment and removal of any air pockets.

TYPICAL PHYSICAL PROPERTIES

TEST PROPERTY	TEST VALUE	TEST PROCEDURE
Thickness (in.)	.027	ASTM D1777
Tensile Strength	MD: 59 lbs CD: 36 lbs	ASTM D5034
Trapezoid Tear	MD: 17 lbs CD: 20 lbs	ASTM D3787



PACKAGING

- 6" x 300' Roll
- 12" x 300' Roll
- 40" x 324' Roll

POLYGLASS U.S.A., INC. MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442
www.polyglass.us

General Line: (888) 410-1375
(954) 233-1330

Customer Service: (800) 222-9782
Technical Service: (866) 802-8017

Questions? technical@polyglass.com

* Primary material manufacturer is Tietex T272 or Equal.

Refer to safety data sheet (SDS) for specific data and handling of our products.

All data furnished refers to standard production using manufacturing testing tolerances. The product user, and not Polyglass, is responsible for determining the suitability and compatibility of our products for the user's intended use.

For the most current product data and warranty information, visit www.polyglass.us

Copyright ©2015 by Polyglass U.S.A., Inc and all rights are reserved
Edition Date: 11/15 • Doc# POLYBRITE POLYESTER FABRIC



1-800-222-9782
www.polyglass.us