

UL Class A Listing for Self-Adhered Assemblies



Committed to Innovation... Dedicated to Adding Value

Polyglass offers more than just world-class modified bitumen membranes. We offer products, systems & certifications...

- UL Class A ratings at lower installed cost
- Available for slopes to 2:12, Combustible Decks, min 15/32" in thickness
- Featuring ADESO® Self-Adhered Dual-Compound technology
- Includes Polyfresko/CURE Kool Roof Solutions
- Options for APP, SBS and Self-Adhered membranes



For more information, contact Polyglass Technical Services Department or visit www.polyglass.us

UL Class A Listing for Self-Adhered Assemblies



UL Product Spec™ - TGFU.R14571

49. **Deck:** C-15/32

Incline: 2

Insulation (Optional): - Polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness.

Base Sheet: - "ELASTOBASE", mechanically fastened or "ELASTOFLEX SA V FR", self-adhered.

Ply Sheet (Optional): - "ELASTOFLEX SA V PLUS FR", "ELASTOFLEX SA V FR" or "ELASTOFLEX SA V FR BASE VENT", self-adhered.

Membrane: - "POLYFLEX SA P FR", "POLYFRESKO G APP SA P FR", "ELASTOFLEX SA P FR", "POLYFRESKO G SBS SA P FR", self-adhered or "DUFLEX G FR", "XtraFlex APP Dual", "POLYFLEX G FR", "XtraFlex APP G HP", "Xtraflex APP G FR", "ELASTOFLEX S6 G FR", "POLYFRESKO G SBS FR", "ELASTOFLEX VG FR", "XtraFlex SBS POLY G", "XtraFlex SBS POLY G T", "XtraFlex SBS GLASS G", "XtraFlex SBS GLASS GT" or "ELASTOSHIELD TS G FR", heat fused.

<http://productspec.ul.com/document.php?id=TGFU.R14571>

For more information, contact Polyglass Technical Services Department or visit www.polyglass.us