

EXISTING TOP OF WALL

POLYGLASS PMMA FLASHING TO PASS THE EDGE OF THE REINFORCEMENT BY NO MORE THAN 1/4"

POLYGLASS PMMA FLASHING TOP COAT

EXISTING ROOF SYSTEM

POLYGLASS PMMA FILLER TYPICAL AT ALL TRANSITION POINTS

POLYGLASS PMMA FLASHING BASE COAT

EMBED POLYGLASS PMMA POLYESTER REINFORCEMENT

EXISTING ROOF CONSTRUCTION

GENERAL NOTATIONS:

1. Metal Edge Flashing, Wood Blockings and Attachments shall comply with ANSI/SPRI ES-1
2. Wood blocking may be slotted for venting of wet-fill decks or other applicable constructions.
3. Cleaning and Preparation - Clean and prepare the surface by brooming mild detergent & water rinse or as required to remove any conditions that could adversely affect the adhesion of primers and liquid materials.
4. Surfaces to receive Polyglass Liquid Flashing System may need to be primed, depending on the surface.
5. Polyglass Liquid Flashing System consists of Polyglass PMMA Flashing Base Coat, embed Polyglass PMMA Polyester Reinforcement covered with Polyglass PMMA Flashing Top Coat.
6. Illustration and notations intended for generalized application only. Please refer to Product Data Sheets for additional information.



polyglass.us

1111 West Newport Center Drive
Deerfield Beach, FL 33442
Technical Service: (866) 794-9659
technical@polyglass.com

Description:

POLYGLASS PMMA PARAPET LOW FLASHING DETAIL (Typical)

SCALE: NTS

Number:

PG-PMMA-WALL-01

Revision Date:

052622