Safety Data Sheet

POLYGLASS PMMA RESIN WINTER GRADE

Safety Data Sheet dated: 11/08/2021 - version 4

Date of first edition: 11/04/2020



1. Identification

Product identifier

Mixture identification:

Trade name: POLYGLASS PMMA RESIN WINTER GRADE

Trade code: 903PA9990

Recommended use and restrictions on use

Recommended use: Coating Restrictions on use: N.A. **Supplier's details**

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency phone number

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. Hazard identification





Classification of the product

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

Harmful to aquatic life

Label elements

Pictograms and Signal Words



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H335 May cause respiratory irritation.

H402 Harmful to aquatic life

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.
P261 Avoid breathing mist/vapours/spray.
P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

Date 11/8/2021 Production Name POLYGLASS PMMA RESIN WINTER GRADE Page n. 1 of 10

| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
|----------------|--|
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P312 | Call a doctor if you feel unwell. |
| P321 | Specific treatment (see supplementary instructions on this label) |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P370+P378 | In case of fire, use a dry powder fire extinguisher to extinguish. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| DEO1 | Dispose of contents/container in accordance with applicable regulations |

P501 Dispose of contents/container in accordance with applicable regulations.

Avoid release to the environment.

Other hazards

P273

None

Ingredient(s) with unknown acute toxicity

None

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. Composition/information on ingredients

Substances

N.A.

Hazardous components within the meaning of WHMIS 2015 and related classification:

List of components

| Concentration (% w/w) | Name | Ident. Numb. | Classification | Registration Number |
|-----------------------|-----------------------|--|--|---------------------|
| 10-20 % | METHYL METHACRYLATE | CAS:80-62-6 | Flam. Liq. 2, H225; STOT SE 3, H335; Skin Irrit. 2, H315; Skin Sens. 1, H317 | |
| 10-20 % | 2-ETHYLHEXYL ACRYLATE | CAS:103-11-7 EC:203-080-7 Index:607-107- 00-7 | Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335; Aquatic Chronic 3, H412; Flam. Liq. 4, H227; Aquatic Acute 2, H401 | |
| 1-2.5 % | TITANIUM DIOXIDE | CAS:13463-67-7 EC:236-675-5 Index:022-006- 00-2 | Carc. 2, H351 | |

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eves contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Date 11/8/2021 **Production Name** POLYGLASS PMMA RESIN WINTER GRADE Page n. 2 of 10 Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

CO2 or Dry chemical fire extinguisher.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Store at below 20 $^{\circ}$ C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

8. Exposure controls/personal protection

Control parameters

List of components with OEL value

| Component METHYL METHACRYLATE | OEL Type OSHA | Country | Ceiling | Long Term mg/m3 410 | Long Term ppm 100 | Short Term mg/m3 | Short Term ppm | Behaviour | Note |
|--------------------------------|---------------------|-------------|---------|------------------------------|----------------------------|------------------------|----------------------|------------|---|
| | ACGIH | | | | 50 | | 100 | | A4 - Not Classifiable as a Human Carcinogen; body weight effects; eye and upper respiratory tract irritation; pulmonary edema; Sensitizer; |
| | EU | | | | 50 | | 100 | Indicative | |
| | MAK | GERMANY | | 210 | 50 | | | | |
| | ACGIH | | | | 50 | | 100 | | A4 - Not Classifiable as a Human Carcinogen; body weight effects; eye and upper respiratory tract irritation; pulmonary edema; dermal sensitizer |
| | MAK | AUSTRIA | | 210 | 50 | 420 | 100 | | |
| | MAK | SWITZERLAND | | 210 | 50 | | | | |
| 2-ETHYLHEXYL ACRYLATE | MAK | GERMANY | | 38 | 5 | | | | |
| | MAK | AUSTRIA | | 82 | 10 | 82 | 10 | | |
| | MAK | SWITZERLAND | | 38 | 5 | | | | |
| | MAK | AUSTRIA | С | | | 82 | 10 | | |
| TITANIUM DIOXIDE | OSHA | | | 15 | | | | | |
| | ACGIH | | | 10 | | | | | A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation; |
| | MAK | GERMANY | | 0.3 | | | | | |
| | ACGIH | | | 10 | | | | | A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation |
| | MAK | AUSTRIA | | 5 | | 10 | | | |
| | MAK | SWITZERLAND | | 3 | | | | | |

Appropriate engineering controls

_ ..

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: viscous liquid

Odour: Like: Ester

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available Initial boiling point and boiling range: 101 °C (214 °F)

Flash point: 35 °C (95 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 1.21 g/cm3 Solubility in water: immiscible Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information on main components of the mixture:

METHYL METHACRYLATE a) acute toxicity LC50 Inhalation Rat = 4632 ppm 4h

LD50 Skin Rabbit 5000 mg/kg

LC50 Inhalation Rat = 7093 ppm 4h

LD50 Oral Rat 8420 mg/kg

2-ETHYLHEXYL ACRYLATE a) acute toxicity LD50 Skin Rabbit = 7522 mg/kg

LD50 Oral Rat = 4435 mg/kg

TITANIUM DIOXIDE a) acute toxicity LD50 Oral Rat > 10000 mg/kg

Substance(s) listed on the IARC Monographs:

METHYL METHACRYLATE Group 3
2-ETHYLHEXYL ACRYLATE Group 2B

Substance(s) listed as OSHA Carcinogen(s):

2-ETHYLHEXYL ACRYLATE TITANIUM DIOXIDE

Substance(s) listed as NIOSH Carcinogen(s):

TITANIUM DIOXIDE

Substance(s) listed on the NTP report on Carcinogens:

None

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of components with eco-toxicological properties

| ziot di componento mun ded to | kicological properti | |
|-------------------------------|---|--|
| Component | Ident. Numb. | Ecotox Infos |
| METHYL METHACRYLATE | CAS: 80-62-6 | a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 243 mg/L 96h EPA |
| | | a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 170 mg/L 96h EPA |
| | | a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss $>$ 79 mg/L 96h IUCLID |
| | | a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = $69 \text{ mg/L } 48 \text{h}$ IUCLID |
| | | a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 170 mg/L 96h IUCLID |
| | | a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 125.5 mg/L 96h EPA |
| | | a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus 153.9 mg/L 96h EPA |
| | | a) Aquatic acute toxicity: LC50 Fish Poecilia reticulata 326.4 mg/L 96h EPA |
| 2-ETHYLHEXYL ACRYLATE | CAS: 103-11-7 - EINECS: 203-080-7 - INDEX: 607-107- 00-7 | a) Aquatic acute toxicity: EC50 Algae Desmodesmus subspicatus = 44 mg/L 72h IUCLID |
| | | a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 47 mg/L 96h IUCLID |
| | | a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 1.81 mg/L 96h ECHA |
| | | a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 17.45 mg/L 48h IUCLID |

Persistence and degradability

N.A

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. Transport information

UN number

TDG-UN number: UN1263 ADR-UN number: 1263 DOT-UN Number: UN1263 IATA-Un number: 1263 IMDG-Un number: 1263

UN proper shipping name

TDG-Shipping Name: PAINT
ADR-Shipping Name: PAINT
DOT-Proper Shipping Name: PAINT
IATA-Technical name: PAINT
IMDG-Technical name: PAINT

Transport hazard class(es)

TDG-Class: 3 ADR-Class: 3

DOT-Hazard Class: 3

IATA-Class: 3
IMDG-Class: 3

Packing group

TDG-Packing Group: III ADR-Packing Group: III DOT Packing Group: III IATA-Packing group: III IMDG-Packing group: III

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions in connection with transport or conveyance

TDG:

TDG Special provisions: 59, 142 Department of Transportation (DOT):

DOT-Special Provision(s): 367, B1, B52, B131, IB3, T2, TP1, TP29

DOT-Label(s): 3
DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A
DOT-Passenger Aircraft: N/A

DOT-Non-Bulk: N/A Road and Rail (ADR-RID) : ADR-Label: 3

DOT-Bulk: N/A

ADR-Hazard identification number: 30

ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA):

IATA-Passenger Aircraft: 355 IATA-Cargo Aircraft: 366 IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3 A72 A192

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 163 223 367 955

IMDG-Page: N/A IMDG-Label: N/A IMDG-EMS: F-E, S-E IMDG-MFAG: N/A

15. Regulatory information

Canada - Federal regulations

DSL - Domestic Substances List

DSL Inventory:

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL Inventory:

No substances listed

NPRI - National Pollutant Release Inventory

Substances listed in NPRI:

No substances listed

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

METHYL METHACRYLATE is listed in TSCA Section 8b
2-ETHYLHEXYL ACRYLATE is listed in TSCA Section 8b
TITANIUM DIOXIDE is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

METHYL METHACRYLATE

Section 313 - Toxic chemical list:

METHYL METHACRYLATE

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

METHYL METHACRYLATE Reportable quantity: 1000 pounds

CAA - Clean Air Act

CAA listed substances:

METHYL METHACRYLATE is listed in CAA Section 112(b) - HAP Section 112(b) - HON

2-ETHYLHEXYL ACRYLATE is listed in CAA Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

METHYL METHACRYLATE is listed in CWA Section 311

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

TITANIUM DIOXIDE Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

METHYL METHACRYLATE

2-ETHYLHEXYL ACRYLATE

TITANIUM DIOXIDE

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

METHYL METHACRYLATE

2-ETHYLHEXYL ACRYLATE

TITANIUM DIOXIDE

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

METHYL METHACRYLATE

2-ETHYLHEXYL ACRYLATE

TITANIUM DIOXIDE

16. Other information

Safety Data Sheet dated: 11/8/2021 - version 4

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

| Code | Description |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H227 | Combustible liquid |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H335 | May cause respiratory irritation. |
| H351 | Suspected of causing cancer. |
| H401 | Toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H412 | Harmful to aquatic life with long lasting effects. |

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

 $\hbox{\tt EINECS: European Inventory of Existing Commercial Chemical Substances}.$

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Date

Paragraphs modified from the previous revision:

- 3. COMPOSITION/INFORMATION ON INGREDIENTS

- 12. ECOLOGICAL INFORMATION

11/8/2021 Production Name POLYGLASS PMMA RESIN WINTER GRADE Page n. 10 of 10