

Safety Data Sheet

FORTRIX PMMA GREY SUMMER GRADE

Safety Data Sheet dated 7/29/2026 version 2

Date of first edition: 04/28/2025

1: Identification

Product identifier

Mixture identification:

Trade name: FORTRIX PMMA GREY SUMMER GRADE

Trade code: 9067434

Recommended use and restrictions on use

Recommended use: resin

Restrictions on use: Not available

Supplier's details

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency phone number

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. Hazard identification



Classification of the product

Flammable Liquids — Category 2

Acute toxicity (oral), Category 4

Skin irritation, Category 2

Skin Sensitization, Category 1B

Highly flammable liquid and vapour.

Harmful if swallowed.

Causes skin irritation.

May cause an allergic skin reaction.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/clothing and eye/face protection.

P301+P312 IF SWALLOWED: Call a doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P330	Rinse mouth.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with applicable regulations.

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

3. Composition/information on ingredients

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of WHMIS 2015 (HPR and its amendments) and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥10 - <15 %	methyl methacrylate; methyl 2-methylprop-2-enoate	CAS:80-62-6 EC:201-297-1 Index:607-035-00-6	Flam. Liq. 2, H225; STOT SE 3, H335; Skin Irrit. 2, H315; Skin Sens. 1B, H317
≥1 - <2.5 %	n,n-bis(2-hydroxypropyl)-p-toluidine; 1,1'-(p-tolylimino)diprop-2-ol	CAS:38668-48-3 EC:254-075-1	Eye Irrit. 2A, H319; Aquatic Chronic 3, H412; Acute Tox. 2, H300
≥0.6 - <1 %	polyethylene glycol diacrylate; 1,2-Ethanediy bisacrylate	CAS:26570-48-9 EC:607-960-5	Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1, H317

The actual concentration of the components listed above is withheld as a trade secret.

Declared percentages are expressed in w/w

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.
- If skin irritation or rash occurs: Get medical advice/attention.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Give nothing to eat or drink.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

- In case of fire, use a dry powder fire extinguisher to extinguish.

CO2 or Dry chemical fire extinguisher.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available

Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Wash skin thoroughly after handling.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Electrical installations / working materials must comply with the technological safety standards.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Temperature of storage facilities must be adequately monitored to avoid hazardous conditions.

Incompatible materials:

Store away from incompatible materials (see Section 10 of the SDS).

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. Exposure controls/personal protection

Control parameters

Occupational Exposure Limits (OEL)

methyl methacrylate; methyl 2-methylprop-2-enoate		
CAS: 80-62-6	ACGIH	Long Term: 50 ppm; Short Term: 100 ppm Notes: DSEN, A4 - URT and eye irr, body weight eff, pulm edema
		Long Term: 50 ppm; Short Term: 100 ppm Notes: A4 - Not Classifiable as a Human Carcinogen;body weight effects;eye and upper respiratory tract irritation;pulmonary edema;dermal sensitizer
		Long Term: 50 ppm; Short Term: 100 ppm Notes: A4 - Not Classifiable as a Human Carcinogen;body weight effects;eye and upper respiratory tract irritation;pulmonary edema;dermal sensitizer
	EU	Long Term: 50 ppm; Short Term: 100 ppm
	MAK AUSTRIA	Long Term: 210 mg/m3 - 50 ppm; Short Term: 420 mg/m3 - 100 ppm
	MAK SWITZERLAND	Long Term: 210 mg/m3 - 50 ppm
	MAK GERMANY	Long Term: 210 mg/m3 - 50 ppm
	OSHA	Long Term: 410 mg/m3 - 100 ppm
		Long Term: 410 mg/m3 - 100 ppm

Predicted No Effect Concentration (PNEC) values

methyl methacrylate; methyl 2-methylprop-2-enoate	
CAS: 80-62-6	Exposure Route: Fresh Water; PNEC Limit: 0.94 mg/l
	Exposure Route: Marine water; PNEC Limit: 0.94 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 5.74 mg/kg
	Exposure Route: Soil; PNEC Limit: 1.47 mg/kg
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

n,n-bis(2-hydroxypropyl)-p-toluidine; 1,1'-(p-tolylimino)dipropan-2-ol	
CAS: 38668-48-3	Exposure Route: Fresh Water; PNEC Limit: 0.017 mg/l
	Exposure Route: Marine water; PNEC Limit: 0.0017 mg/l
	Exposure Route: Marine water sediments; PNEC Limit: 0.00782 mg/kg
	Exposure Route: Freshwater sediments; PNEC Limit: 0.0782 mg/kg

Derived No Effect Level (DNEL) values

methyl methacrylate; methyl 2-methylprop-2-enoate	
CAS: 80-62-6	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 210 mg/m3; Consumer: 200 mg/m3
	Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects Worker Industry: 1.5 mg/cm2; Consumer: 1.5 mg/cm2
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 210 mg/m3; Consumer: 74.3 mg/m3
	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 13.67 mg/kg; Consumer: 8.2 mg/kg
	Exposure Route: Human Dermal; Exposure Frequency: Short Term, local effects Worker Industry: 1.5 mg/cm2; Consumer: 1.5 mg/cm2
n,n-bis(2-hydroxypropyl)-p-toluidine; 1,1'-(p-tolylimino)dipropan-2-ol	
CAS: 38668-48-3	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 2 mg/m3
	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 0.6 mg/kg

Appropriate engineering controls

Not available

Individual protection measures, such as personal protective equipment (PPE)

- Eye protection:
- Use close fitting safety goggles, don't use contact lenses.
- Protection for skin:
- Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
- Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

N.A.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Color:	grey
Odour:	No data available
Melting point / freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	The product is classified Flam. Liq. 2
Upper/lower flammability or explosive limits:	No data available
Flash point:	20 °C (68 °F)
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Kinematic viscosity:	No data available
Viscosity:	No data available
Solubility in water:	No data available
Solubility in oil:	No data available
Partition coefficient (n-octanol/water):	No data available
Vapour pressure:	No data available
Relative density:	1.22 g/cm ³
Relative vapour density:	No data available
Particle characteristics:	
Particle size:	No data available

10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with oxidizing materials. The product could catch fire.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Likely routes of exposure:

Skin contact, skin absorption, eye contact, inhalation and ingestion.

Toxicological Information of the Preparation

a) acute toxicity	The product is classified: Acute toxicity (oral), Category 4(H302) ATEmix - Oral: 1785.71 mg/kg bw ATE Oral = 497.714 mg/kg
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	Not classified Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1B(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

methyl methacrylate; methyl 2-methylprop-2-enoate

CAS: 80-62-6 a) acute toxicity LD50 Oral Rat > 5000 mg/kg
LD50 Skin Rabbit > 5000 mg/kg
LC50 Inhalation Rat = 29.8 mg/l

n,n-bis(2-hydroxypropyl)-p-toluidine; 1,1'-(p-tolylimino)diprop-2-ol

CAS: 38668-48-3 a) acute toxicity LD50 Oral Rat = 25 mg/kg
LD50 Skin Rat > 2000 mg/kg

Substance(s) listed on the IARC Monographs:

methyl methacrylate; methyl 2-methylprop-2-enoate Group 3

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

methyl methacrylate; methyl 2-methylprop-2-enoate

CAS: 80-62-6 a) Aquatic acute toxicity: EC50 Algae = 110 mg/L 72h ECHA
a) Aquatic acute toxicity: EC50 Daphnia magna = 69 mg/L 48h ECHA
a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96h ECHA

n,n-bis(2-hydroxypropyl)-p-toluidine; 1,1'-(p-tolylimino)dipropyl-2-ol

CAS: 38668-48-3 a) Aquatic acute toxicity: LC50 Fish Danio rerio = 17 mg/L 96h ECHA

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. Transport information

UN number

TDG-UN number:

ADR-UN number: 1263

DOT-UN Number: UN1263

IATA-Un number: 1263

IMDG-Un number: 1263

UN proper shipping name

TDG-Shipping Name:

ADR-Shipping Name: PAINT

DOT-Proper Shipping Name: PAINT

IATA-Technical name: PAINT

IMDG-Technical name: PAINT

Transport hazard class(es)

TDG-Class:

ADR-Class: 3

DOT-Hazard Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group

TDG-Packing Group:

ADR-Packing Group: II

DOT Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

Environmental hazards

Marine pollutant: No
Environmental Pollutant: Not Applicable
DOT-RQ: Yes DOT-RQ - Quantity: 1000 lbs
Not Applicable

Special precautions in connection with transport or conveyance

TDG:

TDG Special provisions: 59, 142

Department of Transportation (DOT):

DOT-Special Provision(s): 149, 367, B52, B131, IB2, T4,
DOT-Label(s): 3
DOT-Symbol: N/A
DOT-Cargo Aircraft: 60 L
DOT-Passenger Aircraft: 5 L
DOT-Bulk: 242
DOT-Non-Bulk: 173
DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID) :

ADR-Label: 3
ADR-Hazard identification number: 33
ADR-Transport category (Tunnel restriction code): 2 (D/E)

Air (IATA) :

IATA-Passenger Aircraft: 353
IATA-Cargo Aircraft: 364
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisioning: A3 A72 A192

Sea (IMDG) :

IMDG-Stowage and handling: Category B
IMDG-Segregation: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisioning: 163 367
IMDG-EMS: F-E, S-E

15. Regulatory information**Canada - Federal regulations**

This Safety Data Sheet has been prepared according to the WHMIS Hazardous Products Regulations (SOR/2015-17 as amended by SOR/2022-272).

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory**NPRI (National Pollutant Release Inventory) - List of substances listed.**

No substances listed

USA - Federal regulations**TSCA - Toxic Substances Control Act**

All the components are listed on the TSCA inventory

TSCA listed substances:

methyl methacrylate; methyl 2- is listed in TSCA Section 8b Section 5
methylprop-2-enoate

n,n-bis(2-hydroxypropyl)-p- is listed in TSCA Section 8b
toluidine; 1,1'-(p-
tolylimino)dipropyl-2-ol

polyethylene glycol diacrylate; 1, is listed in TSCA Section 8b Section 5
2-Ethanediy bisacrylate

SARA - Superfund Amendments and Reauthorization Act**Section 302 - Extremely Hazardous Substances:**

No substances listed

Section 304 - Hazardous substances:

methyl methacrylate; methyl 2-methylprop-2-enoate

Section 313 - Toxic chemical list:

methyl methacrylate; methyl 2-methylprop-2-enoate

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

methyl methacrylate; methyl 2-methylprop-2-enoate	Reportable quantity:	1000	pounds
---	----------------------	------	--------

	Reportable quantity for mixture:	7692	pounds
--	----------------------------------	------	--------

CAA - Clean Air Act

CAA listed substances:

methyl methacrylate; methyl 2-methylprop-2-enoate	is listed in CAA	Section 112(b) - HAP	Section 112(b) - HON
---	------------------	----------------------	----------------------

CWA - Clean Water Act

CWA listed substances:

methyl methacrylate; methyl 2-methylprop-2-enoate	is listed in CWA	Section 311
---	------------------	-------------

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

No substances listed

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

methyl methacrylate; methyl 2-methylprop-2-enoate

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

methyl methacrylate; methyl 2-methylprop-2-enoate

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

methyl methacrylate; methyl 2-methylprop-2-enoate

16. Other information

Safety Data Sheet dated: 7/29/2026 - version 2

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code Description

H225	Highly flammable liquid and vapour.
H300	Fatal if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/2/Oral	Acute Tox. 2	Acute toxicity (oral), Category 2
A.2/2	Skin Irrit. 2	Skin irritation, Category 2

A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
B.6/2	Flam. Liq. 2	Flammable Liquids — Category 2
CAN-HAE/C3	Aquatic Chronic 3	Chronic (long-term) aquatic hazard - Category 3

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- Safety Data Sheet
- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION