1: Identification

Product identifier

Mixture identification:

Trade name: PG 350 MOD BIT ADHESIVE

Trade code: 9067035

Recommended use and restrictions on use

Recommended use: Bituminous adhesive solvent based

Restrictions on use: Not available

Supplier's details

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency phone number

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. Hazard identification



Classification of the product

Flammable Liquids — Category 3	Flammable liquid and vapour.
Skin irritation, Category 2	Causes skin irritation.
Eye irritation, Category 2	Causes serious eye irritation.
Carcinogenicity, Category 2	Suspected of causing cancer if inhaled, in contact with skin and if swallowed.
Specific target organ toxicity following repeated exposure, Category 1	Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.
Acute (short-term) aquatic hazard - Category 3	Harmful to aquatic life
Chronic (long-term) aquatic hazard - Category 3	Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer if inhaled, in contact with skin and if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.

P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe mist/vapours/spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/clothing and eye/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P317	If eye irritation persists: Get medical help.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with applicable regulations.

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. Composition/information on ingredients

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of WHMIS 2015 (HPR and its amendments) and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥25 - <30 %	asphalt; bitumen	CAS:8052-42-4 EC:232-490-9	Carc. 2, H351
≥20 - <25 %	petroleum hydrocarbons; Stoddard Solvent	CAS:8052-41-3 EC:232-489-3 Index:649-345-00-4	Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304
≥3 - <5 %	naphthenic oil; Low boiling point naphtha - unspecified	CAS:64742-95-6, 128601-23-0 EC:265-199-0 Index:649-356-00-4	STOT SE 3, H335; STOT SE 3, H336; Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411
≥3 - <5 %	1,2,4-trimethyl-benzene; pseudocumene	CAS:95-63-6 EC:202-436-9 Index:601-043-00-3	Flam. Liq. 3, H226; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Acute Tox. 4, H332
≥1 - <2.5 %	1-propanamine, 3-(isodecyloxy)-, acetate; 3-(Isodecyloxy)propylammonium acetate	CAS:28701-67-9 EC:249-166-8	Acute Tox. 4, H302; Eye Dam. 1, H318; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410
≥0.6 - <1 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350

The actual concentration of the components listed above is withheld as a trade secret.

Declared percentages are expressed in w/w

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

CO2 or Dry chemical fire extinguisher.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available

Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
Wash skin thoroughly after handling.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Handle in a well ventilated place.
Always keep in a well ventilated place.
Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
Store in a well-ventilated place. Keep cool.
Avoid direct exposure to sunlight.
Opened containers must be carefully resealed and kept upright to prevent leakage.
Flammable mixtures may accumulate within the headspace of containers at room temperature.
Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.
Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.
Avoid accumulating electrostatic charge.
Keep away from food, drink and feed.
Electrical installations / working materials must comply with the technological safety standards.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.

Incompatible materials:

Store away from incompatible materials (see Section 10 of the SDS).

Instructions as regards storage premises:

Cool and adequately ventilated.
Safety electric system.

Storage temperature: Not available

---

8. Exposure controls/personal protection

Control parameters

Occupational Exposure Limits (OEL)

asphalt; bitumen

CAS: 8052-42-4	ACGIH		Long Term: 0.5 mg/m3 Notes: (I), A4, BEI - URT and eye irr Long Term: 0.5 mg/m3 Notes: A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free);eye and upper respiratory tract irritation (fume)
	MAK	SWITZERLAND	Long Term: 10 mg/m3
	MAK	GERMANY	Long Term: 1.5 mg/m3

petroleum hydrocarbons; Stoddard Solvent

CAS: 8052-41-3	ACGIH	Long Term: 100 ppm Notes: CNS impairment;eye, kidney and skin damage;nausea; Long Term: 100 ppm Notes: CNS impairment;eye, kidney and skin damage;nausea
	OSHA	Long Term: 2900 mg/m3 - 500 ppm

1,2,4-trimethyl-benzene; pseudocumene

CAS: 95-63-6	EU		Long Term: 100 mg/m3 - 20 ppm
	MAK	AUSTRIA	Long Term: 100 mg/m3 - 20 ppm; Short Term: 150 mg/m3 - 30 ppm
	MAK	GERMANY	Long Term: 100 mg/m3 - 20 ppm

Biological limit values

asphalt; bitumen

CAS: 8052-42-4 Biological Indicator: 1-Hydroxypyrene; Sampling Period: End of turn; End of working week
Medium: Urine
Remark: Not Quantitative

Biological Indicator: 1-Hydroxypyrene; Sampling Period: End of turn; End of working week
Value: 2.5 µg/L; Medium: Urine
Remark: Background

Biological Indicator: 3-Hydroxybenzo(a)pyrene with hydrolysis; Sampling Period: End of turn; End of working week
Medium: Urine
Remark: Not Quantitative

Derived No Effect Level (DNEL) values

asphalt; bitumen

CAS: 8052-42-4 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 2.9 mg/m3; Consumer: 0.6 mg/m3

Appropriate engineering controls

Not available

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Color:	black
Odour:	hydrocarbons like
Melting point / freezing point:	No data available
Initial boiling point and boiling range:	100 °C (212 °F)
Flammability:	Flammable
Upper/lower flammability or explosive limits:	4.05 % w/w
Flash point:	40.5 °C (104.9 °F)
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Kinematic viscosity:	No data available
Viscosity:	41,500.00 mPA-s
Solubility in water:	miscible

Solubility in oil:	immiscible
Partition coefficient (n-octanol/water):	No data available
Vapour pressure:	2.34 (kPa 50°C).
Relative density:	1.00 g/cm3
Relative vapour density:	0.017

Particle characteristics:

Particle size: No data available

10. Stability and reactivity

Reactivity

Stable

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Heat and open flames.

Avoid accumulating electrostatic charge.

Incompatible materials

Water

Avoid contact with oxidizing materials. The product could catch fire.

Hazardous decomposition products

Develop toxic gases when heated to decomposition.

11. Toxicological information

Information on toxicological effects

Likely routes of exposure:

Skin contact, skin absorption, eye contact, inhalation and ingestion.

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2(H319)
d) respiratory or skin sensitisation	Not classified
	Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	The product is classified: Carcinogenicity, Category 2(H351)
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	The product is classified: Specific target organ toxicity following repeated exposure, Category 1(H372)
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

asphalt; bitumen

CAS: 8052-42-4	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg
		LD50 Skin Rabbit > 2000 mg/kg
		LC50 Inhalation Mist Rat > 94.4 mg/l 4h
		LD50 Skin Rabbit > 2000 mg/kg

		LC50 Inhalation Rat > 94.4 mg/m3 4.5h
		LD50 Oral Rat > 5000 mg/kg
		LC50 Inhalation Rat > 94.4 mg/m3 4.5h
		LD50 Oral Rat > 5000 mg/kg
	i) STOT-repeated exposure	NOAEL Skin Rat = 200 mg/kg Notes: 90 d
		NOAEC Inhalation Mist Rat = 20.1 mg/l Notes: 90 d

petroleum hydrocarbons; Stoddard Solvent

CAS: 8052-41-3	a) acute toxicity	LD50 Skin Rabbit > 3000 mg/kg
		LC50 Inhalation Rat > 5.5 mg/l 4h

naphthenic oil; Low boiling point naphtha - unspecified

CAS: 64742-95-6, 128601-23-0	a) acute toxicity	LD50 Skin Rabbit > 2000 mg/kg
		LD50 Oral Rat = 3492 mg/kg
		LC50 Inhalation Vapour Rat = 6193 mg/m3

1,2,4-trimethyl-benzene; pseudocumene

CAS: 95-63-6	a) acute toxicity	LD50 Skin Rabbit > 3160 mg/kg
		LC50 Inhalation Rat = 18 g/m3 4h
		LD50 Oral Rat = 3280 mg/kg

1-propanamine, 3-(isodecyloxy)-, acetate; 3-(Isodecyloxy)propylammonium acetate

CAS: 28701-67-9	a) acute toxicity	LD50 Oral Rat = 1216 mg/kg

silica sand; quartz

CAS: 14808-60-7	a) acute toxicity	LD50 Oral > 2000 mg/kg
		LD50 Skin > 2000 mg/kg

Substance(s) listed on the IARC Monographs:

asphalt; bitumen	Group 2B
silica sand; quartz	Group 1

Substance(s) listed as OSHA Carcinogen(s):

asphalt; bitumen

silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

asphalt; bitumen

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of Eco-Toxicological properties of the product

The product is classified: Acute (short-term) aquatic hazard - Category 3(H402), Chronic (long-term) aquatic hazard - Category 3(H412)

List of Eco-Toxicological properties of the components

asphalt; bitumen

CAS: 8052-42-4	a) Aquatic acute toxicity: LC50 Fish = 1000 mg/L
	b) Aquatic chronic toxicity: NOEC Fish = 1000 mg/L - 28 d

naphthenic oil; Low boiling point naphtha - unspecified

CAS: 64742-95-6, 128601-23-0	a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss = 9.22 mg/L 96h IUCLID
	a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 21.3 mg/L 48h IUCLID

1,2,4-trimethyl-benzene; pseudocumene

CAS: 95-63-6 G: LC50 Avian Colinus virginianus > 6500 ppm 5d IUCLID

G: LD50 Avian Colinus virginianus > 2250 mg/kg IUCLID

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 7.19 mg/L 96h EPA

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 6.14 mg/L 48h IUCLID

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. Transport information

UN number

TDG-UN number: UN1993

ADR-UN number: 1993

DOT-UN Number: NA1993

IATA-Un number: 1993

IMDG-Un number: 1993

UN proper shipping name

TDG-Shipping Name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - trimethylbenzene)

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - trimethylbenzene)

DOT-Proper Shipping Name: Combustible liquid, n.o.s. (solvent naphtha - trimethylbenzene)

IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - trimethylbenzene)

IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - trimethylbenzene)

Transport hazard class(es)

TDG-Class: 3

ADR-Class: 3

DOT-Hazard Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group

TDG-Packing Group: III

ADR-Packing Group: III

DOT Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: Yes DOT-RQ - Quantity: 100 lbs

Not Applicable

Special precautions in connection with transport or conveyance

TDG:

TDG Special provisions: 16,150 N/A

Department of Transportation (DOT):

DOT-Special Provision(s): 148, IB3, T1, TP1

DOT-Label(s): 3

DOT-Symbol: D G

DOT-Cargo Aircraft: 220 L

DOT-Passenger Aircraft: 60 L

DOT-Bulk: 241

DOT-Non-Bulk: 203

DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID) :

ADR-Label: 3

ADR-Hazard identification number: 30

ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA) :

IATA-Passenger Aircraft: 355

IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3

Sea (IMDG) :

IMDG-Stowage and handling: Category A

IMDG-Segregation: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 223 274 955

IMDG-EMS: F-E, S-E

Pursuant to 49 CFR 173.120(b)(2) and 49 CFR 173.150(f) a flammable liquid with a flash point at or above 100 degrees Fahrenheit may be reclassed as a combustible liquid for transportation within the U.S. by motor vehicle or rail only.

---

15. Regulatory information

Canada - Federal regulations

This Safety Data Sheet has been prepared according to the WHMIS Hazardous Products Regulations (SOR/2015-17 as amended by SOR/2022-272).

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

asphalt; bitumen	is listed in TSCA	Section 8b
petroleum hydrocarbons; Stoddard Solvent	is listed in TSCA	Section 8b
naphthenic oil; Low boiling point naphtha - unspecified	is listed in TSCA	Section 8b
1,2,4-trimethyl-benzene; pseudocumene	is listed in TSCA	Section 8b

1-propanamine, 3-(isodecyloxy)-, acetate; 3-(Isodecyloxy)propylammonium acetate	is listed in TSCA	Section 8b
silica sand; quartz	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

1,2,4-trimethyl-benzene; pseudocumene

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

1,2,4-trimethyl-benzene; pseudocumene	is listed in CAA	Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

asphalt; bitumen	Listed as carcinogen
silica sand; quartz	Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

asphalt; bitumen

petroleum hydrocarbons; Stoddard Solvent

1,2,4-trimethyl-benzene; pseudocumene

silica sand; quartz

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

asphalt; bitumen

petroleum hydrocarbons; Stoddard Solvent

1,2,4-trimethyl-benzene; pseudocumene

silica sand; quartz

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

asphalt; bitumen

petroleum hydrocarbons; Stoddard Solvent

1,2,4-trimethyl-benzene; pseudocumene

silica sand; quartz

---

16. Other information

Safety Data Sheet dated: 8/26/2026 - version 5

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
A.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3
CAN-HAE/A1	Aquatic Acute 1	Acute (short-term) aquatic hazard - Category 1
CAN-HAE/C1	Aquatic Chronic 1	Chronic (long-term) aquatic hazard - Category 1
CAN-HAE/C2	Aquatic Chronic 2	Chronic (long-term) aquatic hazard - Category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
IMDG: International Maritime Code for Dangerous Goods.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
CLP: Classification, Labeling, Packaging.
EINECS: European Inventory of Existing Commercial Chemical Substances.
INCI: International Nomenclature of Cosmetic Ingredients.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
GefStoffVO: Ordinance on Hazardous Substances, Germany.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
DNEL: Derived No Effect Level.
PNEC: Predicted No Effect Concentration.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 14. TRANSPORT INFORMATION